Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (original). Apparatus for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

means for dividing the audio signal into at least two subband signals;

means for examining at least one sub-band signal with regard to a periodicity in the at least one sub-band signal by an autocorrelation function, to obtain rhythm raw-information for the sub-band signal, wherein a delay is associated to a peak of the autocorrelation function;

means for postprocessing the rhythm raw-information for the sub-band signal determined by the autocorrelation function, to obtain postprocessed rhythm raw-information for the sub-band signal, so that in the postprocessed rhythm raw-information an ambiguity in an integer plurality of a delay, to which an autocorrelation function peak is associated, is reduced, or a signal portion is added at an integer fraction of a delay, to which an autocorrelation function peak is associated; and

means for establishing the rhythm information of the audio signal by using the postprocessed rhythm raw-information of the sub-band signal and by using another sub-band signal of the at least two sub-band signals.

BEST AVAILABLE COPY

Page 2 of 8

Claim 2 (currently amended). Apparatus according to claim 1, wherein the means for postprocessingcomprises postprocessing comprises:

means for calculating a version of the rhythm rawinformation of a sub-band signal spread by an integer factor; and

means for subtracting the version of the rhythm rawinformation of the sub-band signal spread by an integer factor larger than one, or a version of the rhythm rawinformation of the sub-band signal derived from this version, to obtain the postprocessed rhythm rawinformation for the sub-band signal.

Claim 3 (original). Apparatus according to claim 2, wherein means for subtracting is disposed to perform, prior to subtracting, a weighting of the spread version with a factor between zero and one, to generate the derived version.

Claim 4 (original). Apparatus according to claim 1, wherein means for postprocessing comprises:

means for calculating a version of the rhythm rawinformation compressed by an integer factor larger than one; and

means for adding the compressed version of the rhythm rawinformation of the sub-band signal or a version derived therefrom to the rhythm raw-information of the sub-band signal, to obtain the postprocessed rhythm raw-information for the sub-band signal.

Claim 5 (original). Apparatus according to claim 4, wherein the means for adding is disposed to perform, prior to adding, a weighting of the compressed version of the

Page 3 of 8

rhythm raw-information by a factor between zero and one, such that a weighted compressed version of the rhythm raw-information is added to the rhythm raw-information of the sub-band signal to generate the derived version.

Claim 6 (original). Apparatus according to claim 1, further comprising:

means for evaluating a quality of the periodicity of the postprocessed rhythm raw-information, to obtain a significance measure for the sub-band signal,

wherein means for establishing is further disposed to establish the rhythm information of the audio signal by considering the significance measure of the sub-band signal.

Claim 7 (original). Method for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

dividing the audio signal into at least two sub-band signals,

examining at least one sub-band signal with regard to a periodicity in the at least one sub-band signal by an autocorrelation function, to obtain rhythm raw-information for the sub-band signal, wherein a delay is associated to a peak of the autocorrelation function;

postprocessing the rhythm raw-information for the sub-band signal determined by the autocorrelation function, to obtain postprocessed rhythm raw-information for the sub-band signal, so that in the postprocessed rhythm raw-information an ambiguity in the integer plurality of a delay, to which an autocorrelation function peak is associated, is reduced, or a signal portion is added at an

Page 4 of 8

integer fraction of a delay, to which an autocorrelation function peak is associated; and

establishing the rhythm information of the audio signal by using the postprocessed rhythm raw-information of the sub-band signal and by using a further sub-band signal of the at least two sub-band signals.

Claim 8 (currently amended). Apparatus for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

means for examining the audio signal with regard to a periodicity in the audio signal, to obtain rhythm raw-information for the audio signal, wherein a delay is associated to a peak of the autocorrelation function;

means for postprocessing the rhythm raw-information for the audio signal determined by the autocorrelation function, to obtain postprocessed rhythm raw-information for the audio signal by adding a version of the rhythm raw information forged by an integer factor, so that in the postprocessed rhythm raw-information a signal portion is added at an integer fraction of a delay, to which an autocorrelation function peak is associated; and

means for establishing rhythm information of the audio signal by using the postprocessed rhythm raw-information of the audio signal.

Claim 9 (original). Apparatus for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

means for examining the audio signal with regard to a periodicity in the audio signal, to obtain rhythm raw-

Page 5 of 8

information for the audio signal, wherein a delay is associated to a peak of the autocorrelation function;

means for postprocessing the rhythm raw-information for the audio signal determined by the autocorrelation function, to obtain postprocessed rhythm raw-information for the audio signal, by subtracting a version of the rhythm raw-information weighted by a factor unequal one and spread by an integer factor larger than one; and

means for establishing the rhythm information of the audio signal by using the postprocessed rhythm raw-information of the audio signal.

Claim 10 (currently amended). Method for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

examining the audio signal with regard to a periodicity in the audio signal, to obtain rhythm raw-information for the audio signal, wherein a delay is associated to a peak of the autocorrelation function;

postprocessing the rhythm raw-information for the audio signal by the autocorrelation function, to obtain postprocessed rhythm raw-information for the audio signal by adding a version of the rhythm raw information forged by an integer factor, so that in the postprocessed rhythm raw-information a signal portion is added at an integer fraction of a delay, to which an autocorrelation function peak is associated; and

establishing the rhythm information of the audio signal by using the postprocessed rhythm raw-information of the audio signal.

Claim 11 (original). Method for analyzing an audio signal with regard to rhythm information of the audio signal by using an autocorrelation function, comprising:

examining the audio signal with regard to a periodicity in the audio signal, to obtain rhythm raw-information for the audio signal, wherein a delay is associated to a peak of the autocorrelation function;

postprocessing the rhythm raw-information for the audio signal determined by the autocorrelation function, to obtain postprocessed rhythm raw-information for the audio signal, by subtracting a version of the rhythm raw-information weighted with a factor unequal one and spread by an integer factor larger than one; and

establishing the rhythm information of the audio signal by using the postprocessed rhythm raw-information of the audio signal.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.